

























Product	Part No	Description	Pack Qty
	0-097-60	Commercial rear lamp, 12/24 volt LED, universal fitting. Stop / tail / direction indicator. I 140 x w 82 x h 140mm. ECE approved.	box 1
	0-097-98	Mounting bezel for surface mounting of the above.	bag 1
	0-097-68	Commercial 12/24 volt LED reverse lamp with stud fixing. Black plastic body. I 140 x w 82 x h 140mm. ECE approved	box 1
	0-097-98	Mounting bezel for surface mounting of the above.	bag 1
	0-081-98	Commercial trailer lamp lens, right hand. Stop/tail/direction indicator/fog/reverse/reflex reflector. I 400 x w 75 x h 158mm. ECE approved.	bag 1
	0-081-99	Left hand version of the above.	bag 1
	0-294-75	Rear lamp, stop/tail/direction indicator. 12/24 volt LED. I 95 x w 32 x h 95mm. ECE and EEC approved.	box 1
	0-294-70	Trailer rear lamp, right hand. Stop/tail/fog/direction indicator/reflex reflector. 12 volt LED with bulb type Fog lamp. I 157 x w 54 x h 217mm. ECE approved.	box 1
	0-294-71	Left hand version of the above.	box 1
	0-453-75	Black plastic number plate lamp. 12/24 volt LED. I 120 x w 42 x h 47mm. EEC and ECE approved.	bag 1
  	0-170-30	Amber LED side marker lamp. 12/24 volt with leads. I 55 x w 27 x h 35mm. EEC and ECE approved.	bag 1
	0-170-20	Clear LED front marker version of above.	bag 1
	0-170-25	Red LED rear marker version of above.	bag 1


new

Product	Part No	Description	Pack Qty
	0-170-10	Amber LED side marker lamp. 12/24 volt. Requires connector 0-011-62. I 71 x w 25 x h 42mm. EEC and ECE approved.	bag 1
	0-170-04	Green LED ABS marker version of above.	bag 1
	0-170-70	Amber LED side marker lamp. 12/24 volt with leads. I 111 x w 22 x h 50mm. EEC and ECE approved.	box 1
	0-170-60	Clear LED front marker version of above.	box 1
	0-170-65	Red LED rear marker version of above.	box 1
	0-170-99	Vertical mounting bracket for all the above lamps.	Bag 1
	0-420-50	A powerful and compact single 10 watt 9-50 volt LED work lamp, produces 100 watt halogen equivalent. Low current draw, 0.75 amp at 12 volt dc. Black powder coated die cast aluminium case, polycarbonate lens, supplied with stainless steel adjustable bracket and sealed connector socket/plug. The lamp can be linked with additional units to form a multiple unit. Protected to IP 68. I 52 x w 52 x h 83mm.	clam 1
	0-420-60	A powerful and compact twin 3 watt 12/24 volt LED work lamp. Low current draw, 0.9 amp at 12 volt dc. Polymer housing, supplied with stainless steel bracket, 250mm flying lead. Protected to IP66. I 93 x w 56 x h 81mm.	box 1
	0-420-70	A powerful and compact quad 3 watt 12/24 volt LED work lamp. Low current draw, 1.4 amp at 12 volt dc. Polymer housing, supplied with stainless steel bracket, 2m lead. Protected to IP66. I 110 x w 84 x h 139mm.	box 1
	0-669-12	LED flexible light strip, 12 volt, adhesive backed. 60 super bright white LEDs per meter, can be cut and wired every 3 LEDs (requires soldering), waterproof.	bag 1 metre
	0-669-13	LED map light, 12 volt, 12 super bright white LEDs with 6 red LED night light facility. Switch on lamp head with 325mm flexible arm. CE approved.	card 1







Product	Part No	Description	Pack Qty
 	0-364-11	On/off or change over, single pole switch with plastic paddle style lever and 6.3mm blade terminals. 14.5mm panel hole. 5 amps at 12 volts dc rating. Replaces SPB200.	bag 1
 	0-658-11	On/on or change over, single pole switch with plastic paddle style lever and 6.3mm blade terminals. 14.5mm panel hole. 18 amps at 12 volts dc rating. Replaces 34889.	bag 1
 	0-687-11	Momentary on, single pole switch with plastic paddle style lever and 6.3mm blade terminals. 14.5mm panel hole. 5 amps at 12 volts dc rating. Replaces SPB204.	bag 1
 	0-349-11	On/off/on or change over, single pole switch with plastic paddle style lever and 6.3mm blade terminals. 14.5mm panel hole. 10 amps at 12 volts dc rating. Replaces 31743.	bag 1
 	0-645-11	On/on/on, single pole switch with plastic paddle style lever and 6.3mm blade terminals. 14.5mm panel hole. 10 amps at 12 volts dc rating. Replaces 35927 and 31788.	bag 1
 	0-496-61	Change over or on/off/momentary on or momentary change over, three position, single pole miniature lever switch with chrome plated lever and silver plated solder lug terminals. 6.5mm panel hole. 5 amps at 28 volts dc rating. Protected to IP67.	bag 1
 	0-645-70	Off/side/dip/main headlamp rotary switch with horn push. 20/4 amp at 12 volts dc rating, 5/2 amp at 24 volt dc rating. 6.3mm blade terminals, 14mm panel hole.	box 1
 	0-484-50	Hazard warning light switch, push-on/push-off with 12 volt 1.2 watt panel bulb illumination. 7 x 6.3mm blade terminals, 30mm panel hole.	box 1

new

Product	Part No	Description	Pack Qty																				
 <table border="1"> <thead> <tr> <th>TERMS</th> <th>0</th> <th>1</th> <th>1+2</th> <th>2</th> </tr> </thead> <tbody> <tr> <td>A-1</td> <td></td> <td>■</td> <td></td> <td></td> </tr> <tr> <td>A-1-2</td> <td></td> <td></td> <td>■</td> <td></td> </tr> <tr> <td>A-2</td> <td></td> <td></td> <td></td> <td>■</td> </tr> </tbody> </table>	TERMS	0	1	1+2	2	A-1		■			A-1-2			■		A-2				■	0-605-09	Marine battery isolator with fixed control knob. Rated at 300 amps continuous (1hr) at 48 volts dc and 1000 amps for 5 seconds. Selects between batteries one, two, both or off. M10 studs. I 69 x w 77 x h 69mm. CE approved.	box 1
TERMS	0	1	1+2	2																			
A-1		■																					
A-1-2			■																				
A-2				■																			
 <table border="1"> <thead> <tr> <th>TERMS</th> <th>Clip on</th> <th>Knob press (Clip on)</th> <th>Clip off</th> </tr> </thead> <tbody> <tr> <td>C-C</td> <td></td> <td>■</td> <td>■</td> </tr> <tr> <td>M-M</td> <td>■</td> <td></td> <td></td> </tr> </tbody> </table>	TERMS	Clip on	Knob press (Clip on)	Clip off	C-C		■	■	M-M	■			0-605-41	Marine emergency cut-off switch with lanyard, cut-out can also be operated with lanyard clip in place by pressing knob, suitable for coil or magneto ignition. 6.3mm blade terminals, 16mm panel hole. 15 amps at 12 volts dc rating.	box 1								
TERMS	Clip on	Knob press (Clip on)	Clip off																				
C-C		■	■																				
M-M	■																						
	0-003-70	Black plastic insulator boot, cable entry 8mm diameter, terminal hole 17mm diameter.	bag 10																				
	0-003-75	Red version of the above.	bag 10																				
	0-003-80	Black plastic insulator boot, cable entry 17mm diameter, terminal hole 17mm diameter.	bag 10																				
	0-003-85	Red version of the above.	bag 10																				
	0-999-63	13 core, 8 x 30/0.30mm 1.5mm ² and 5 x 50/0.30mm 2.5mm ² (thin wall). Red, brown, green, yellow, blue, black, pink, white/blue, grey, orange, white, white/red, white/black. ISO 11446:2004	coil 10 m																				
	0-237-06	Fuse box, 4 way, for 29mm glass fuses with storage for 2 spare fuses. Through panel mounting, 6.3mm blade terminals. Supplied without fuses. Replaces 6FJ, 37409 and 37564.	bag 1																				
	0-237-07	Fuse box, 4 way, for 29mm glass fuses with storage for 2 spare fuses. Surface mounting, 6.3mm blade terminals. Supplied without fuses. Replaces 7FJ, 37420 and 37552.	bag 1																				
	0-642-30	Disc horn, electronic, contactless 2 pole. 108dB(A) Diaphragm type with passivated steel body. Supplied with mounting strap. 90mm diameter. CE approved.	clam 1																				

Product	Part No	Description	Pack Qty
	0-777-15	15 core retractable cable, black hytel sheathed 3 metre working length. 3 x 2.50mm ² white, orange, white/red, 10 x 1.50mm ² yellow, green, blue, black, brown, red, pink, grey, white/black, white/blue, 2 x 1.50mm ² white/green and white/brown twisted pair. PVC insulated cores.	bag 1
	0-479-67	15 pole plug adapter, 15 pole socket to 2 x 7 pole plugs (24N and 24S) to ISO 12098. Additional 3 data wires are installed but not connected.	box 1
	0-521-03	Trailer socket bracket, 16 swg galvanised mild steel for 13 pin single socket.	card 1
	0-289-53	Trailer socket bracket assembly with 13 pin plastic socket and 1 metre of 13 core cable. ISO 11446.	bag 1
	0-776-03	Colour CMOS miniature camera with sun visor clip. Plastic housing. F2.5 lens with 120° horizontal view. Protected to IP68. Ø 24 x w 42mm.	box 1
	0-776-05	Colour CMOS camera for left hand side mounting. Plastic housing. F2.5 lens with 120° vertical view. Protected to IP68. l 40 x w 75 x h 62mm.	box 1
	0-776-06	As above for right hand side mounting.	box 1
	0-776-13	Colour infra red CMOS camera for side or rear mounting. Metal housing. F2.5 lens with 110° vertical view. Protected to IP68. l 69 x w 123 x h 65mm.	box 1
	0-776-90	Mobile DVR recorder, 12 volt, stores single camera video onto compact flash card (not included). Playback on screen or computer, with time, vehicle, driver information, image quality and frames per second selectable in user set up. Supplied with computer software, wiring harness, mounting bracket and remote control; can be used with any Durite colour camera. Typical recording time with a 4Gb flash card and super quality set is 13 hours at 2 frames per second (fps) and 1 hour at 30 fps. l 96 x w 164 x h 27mm. CE and ECE approved.	box 1
	0-727-33	Voltage sensitive relay, 12 volt 140 amp with red LED indicator. Allows split charging of second battery bank without discharging the primary/start battery, relay makes at 13.3 volts and breaks at 12.8 volt. l 68 x w 54 x h 68mm. CE approved.	box 1

new

Product	Part No	Description	Pack Qty
	0-335-58	12 volt bulk head change over/reversing solenoid. Isolated return. Rated at 100 amp intermittant at 12 volts. M8 studs and 6.3mm blade terminals.	box 1
 	0-133-30 12 volt	Pre-heat relay, with post heat. Replacing:- GM 91167210, 9201699 Nagares BED712 Opel 4409990, 4506156 Renault 7700115078	card 1
	0-132-39 0-132-40 0-132-41 0-132-42 0-132-43 0-132-44 0-132-45 0-132-46	Glow plugs: Audi, Seat, Skoda, Volkswagen. BMW. Audi, Mitsubishi, Seat, Skoda, Volkswagen. Audi, Volkswagen. Citroen, Ford, Mazda, Peugeot, Suzuki, Volvo. Fiat, Lancia, Opel, Suzuki, Vauxhall. Citroen, Jaguar, Volvo. Alfa, Fiat, Opel, Saab, Vauxhall	card 1
		For applications and cross references see Section 7.	
	0-703-98	Screw starter, aluminium shaft, steel drives for cross head and flat head screws, includes pen clip. Length 154mm.	card 1
	0-703-90	Heavy duty crimping tool, sprung loaded punch, crimping can be acheived in vice or with hammer. Suitable for our copper tube connectors up to cable CSA of 95mm ² .	bag 1
	0-647-06 0-647-10 0-647-55	Automatic automotive battery charger for all lead/acid batteries, including sealed for life, gel and maintenance free. Features include: micro chip controlled three stage charging, allowing the charger to be left permanently connected to maintain a fully-charged status without harming the battery. On/off switch, detachable wall-mount brackets, supplied with crocodile clips and leads.	box 1 box 1 box 1
	0-647-20 0-647-60	Automatic automotive battery charger for all lead/acid batteries, including sealed for life, gel and maintenance free. Features include: micro chip controlled three stage charging, allowing the charger to be left permanently connected to maintain a fully-charged status without harming the battery. On/off switch, detachable wall-mount brackets, supplied with crocodile clips and leads.	box 1 box 1